

COMPRESSOR DEFINITION

Designation	NE U2140GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	958JA71

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expantion device	Capillary tube or Expansion valve		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	8.77	[cm ³] (0.535 cu.in)
2.1 Bore [mm]	26.497	
2.2 Stroke [mm]	15.920	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.6	[kg] (23.37 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-0025-65	
3 Start capacitor	64-77(330)	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	4TM757JDB	
6 Start winding resistance	24.26	[Ωat 25°C (77°F)] +/- 8%
7 Run winding resistance	7.79	[Ωat 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	13.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	2.63	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1660	418	486	357	2.06	11.25	4.65	1.17	1.36

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	799	201	234	205	1.52	5.37	3.89	0.98	1.14
-35	(-31)	1049	264	307	238	1.61	7.08	4.42	1.11	1.29
-30	(-22)	1368	345	401	272	1.72	9.26	5.04	1.27	1.48
-25	(-13)	1755	442	514	305	1.83	11.92	5.75	1.45	1.69
-20	(- 4)	2210	557	648	339	1.95	15.09	6.53	1.65	1.91
-15	(+ 5)	2733	689	801	371	2.07	18.78	7.36	1.86	2.16
-10	(+14)	3323	837	974	403	2.20	22.99	8.23	2.07	2.41

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	728	183	213	209	1.52	4.88	3.48	0.88	1.02
-35	(-31)	971	245	285	246	1.63	6.54	3.96	1.00	1.16
-30	(-22)	1281	323	375	284	1.76	8.65	4.50	1.13	1.32
-25	(-13)	1655	417	485	325	1.90	11.22	5.09	1.28	1.49
-20	(- 4)	2095	528	614	367	2.06	14.28	5.71	1.44	1.67
-15	(+ 5)	2600	655	762	410	2.23	17.83	6.34	1.60	1.86
-10	(+14)	3169	799	929	455	2.41	21.88	6.98	1.76	2.05

TEST CONDITIONS: @220V50Hz		ASHRAE32 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	637	160	187	209	1.52	4.26	3.04	0.77	0.89
-35	(-31)	869	219	255	249	1.64	5.84	3.49	0.88	1.02
-30	(-22)	1165	294	341	293	1.79	7.85	3.97	1.00	1.16
-25	(-13)	1523	384	446	341	1.96	10.30	4.46	1.13	1.31
-20	(- 4)	1943	490	569	393	2.16	13.21	4.95	1.25	1.45
-15	(+ 5)	2425	611	711	448	2.38	16.59	5.42	1.37	1.59
-10	(+14)	2970	748	870	506	2.63	20.46	5.86	1.48	1.72

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		